


# SPECIAL FLUIDS HOT WATER AND STEAM

## Product Index



Function	Δ P		Temperature		Pipe connections	Series	Page
	min. (bar)	max. (bar)	min. (°C)	max. (°C)			
<b>SOLENOID VALVES, BRASS BODY</b>							
2/2 NC	0	6	-20	+160/165	 1/4 - 3/8	263	V901-09
2/2 NC	0/0,3	10	-20	+177	3/8 .. 1	220	V901-11
2/2 NC	0	9	-20	+150	3/8 .. 3/4	222	V901-15
2/2 NC	0,35	10	-20	+184	1 1/4 .. 2	220	V901-25
<b>PRESSURE OPERATED VALVES, BRONZE BODY</b>							
2/2 NC-NO	0	16	-10	+184	3/8 .. 2 1/2	E290	V901-46-1
2/2 NC-NO	0	16	-10	+184	Flanged DN 25 .. 50	T290	V901-46-1
2/2 NC-NO	0	16	-10	+184	1/2 .. 2	165 (AD/TBT)	V901-46-3
2/2 NC	0	16	-10	+184	Flanged DN 15 .. 80	165 (AD/BBT)	V901-46-3
3/2 NC-NO	0	16	-10	+184	1/2 .. 2	E390	V901-46-1
3/2 NO	0	16	-10	+184	1/2 .. 2	166 (AD/TBT)	V901-46-3
<b>PRESSURE OPERATED VALVES, STAINLESS STEEL BODY</b>							
2/2 NC-NO	0	16	-10	+184	3/8 .. 2 1/2	E290	V901-46-1
2/2 NC-NO	0	16	-10	+184	External thread 1/2 .. 1	U290	V901-46-1
2/2 NC-NO	0	16	-10	+184	External thread, food connections DIN 11851 Rd 28x8 .. 44x6	Y290	V901-46-1
2/2 NC-NO	0	16	-10	+184	Clamp / butt welding DN 10 .. 65	S290	V901-46-1
2/2 NC-NO	0	40	-25	+250	1/2 .. 2	E298	V901-46-2
2/2 NC-NO	0	40	-25	+250	Flanged (DIN and ANSI Class 300) DN 15..50	T298	V901-46-2
2/2 NC-NO	0	40	-25	+250	Socket welding ends DN 15..50	S298	V901-46-2
3/2 U	0	40	-25	+250	1/2 .. 2	E398	V901-46-2
3/2 U	0	40	-25	+250	Flanged (DIN and ANSI Class 300) DN 15..50	T398	V901-46-2
3/2 U	0	40	-25	+250	Socket welding ends DN 15..50	S398	V901-46-2
2/2 NC-NO	0	24	-10	+240	External thread M25x1,5..M36x2	R298	V901-54
2/2 NC-NO	0	24	-10	+240	Pad mounting DN 10 .. 32	R298	V901-56

00098GB-2016/R02  
Availability, design and specifications are subject to change without notice. All rights reserved.

