

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

# Conductivity Standard 100 mS/cm

Material number 238935

Revision date: 28.03.2012 Version: Language: en-US Date of print: 06.03.2014

Page: 1 of 5

# 1. Product and company identification

#### **Product identifier**

Trade name: Conductivity Standard 100 mS/cm

#### Relevant identified uses of the substance or mixture and uses advised against

General use: Calibration of conductivity sensors

## Details of the supplier of the safety data sheet

HAMILTON Bonaduz AG Company name:

Via Crusch 8 Street/POB-No.: 7402 Bonaduz Postal Code, city:

Switzerland

www: www.hamilton.ch +41 81 660 62 76 Telephone: +41 81 660 60 70 Telefax:

Dept. responsible for information:

Susanne Näf-Rüdiger,

Telephone: +41 81 660 62 76, E-mail SNaef@hamilton.ch

#### **Emergency telephone number**

GIZ-Nord, Germany, Telephone: +49 (0)551-19240

## 2. Hazards identification

#### **Emergency overview**

Physical state: liquid Appearance:

Color: colorless

Odor odorless

#### Regulatory status

This material is not considered hazardous by the U.S. OSHA Hazard Communication Standard

(29 CFR 1910.1200) and SIMDUT in Canada.

#### Information pertaining to special dangers for human and environment

see section 11: Toxicological information

# 3. Composition / Information on ingredients

Aqueous solution of anorganic salts and organic compounds. Chemical characterization:

Contains Glycerol: The maximum workplace exposure limits are expressed in Section 8, as Additional information:

may be required.

## 4. First-aid measures

Move victim to fresh air. In case of respiratory difficulties seek medical attention. In case of inhalation:

In case of skin contact: Remove residues with soap and water.

Change contaminated clothing. In case of skin reactions, consult a physician.



accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Conductivity Standard 100 mS/cm

Revision date: 28.03.2012 Version: Language: en-US

Date of print: 06.03.2014

2 of 5

Page:

Immediately flush eyes with plenty of flowing water for 10 to 15 minutes holding eyelids apart.

Subsequently consult an ophthalmologist.

Material number 238935

Rinse mouth and drink large quantities of water. Induce vomiting when the affected person is After swallowing:

not unconscious. If you feel unwell, seek medical advice.

#### Most important symptoms and effects, both acute and delayed

no data available

#### Information to physician

Treat symptomatically.

# 5. Firefighting measures

Flash point/flash point range:

After eye contact:

approx. 180 °C

Suitable extinguishing media:

Product is non-combustible. Extinguishing materials should therefore be selected according to surroundings.

#### Special hazards arising from the substance or mixture

In the event of a fire, the following may be produced when the water evaporates: Carbon monoxide and carbon dioxide.

Special protective equipment for firefighters:

Wear self-contained breathing apparatus. Wear suitable protective clothing.

#### 6. Accidental release measures

Avoid contact with the substance. Do not breathe vapors. Provide adequate ventilation. Remove Personal precautions:

all sources of ignition.

Environmental measures: Do not allow to penetrate into soil, waterbodies or drains.

Methods for cleaning up: Soak up with absorbent materials such as sand, siliceus earth, acid- or universal binder. Store

in special closed containers and dispose of according to ordinance. Wash spill area with plenty

of water.

# 7. Handling and storage

#### Handling

Advices on safe handling: Avoid contact with skin and eyes. Do not breathe vapors.

Provide adequate ventilation.

#### Storage

Requirements for storerooms and containers:

Keep container tightly closed. Store at room temperature. (Recommendation: 15 - 25 °C)

#### Specific use(s)

Calibration of conductivity sensors



Material number 238935

in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Conductivity Standard 100 mS/cm

Revision date: 28.03.2012 Version: Language: en-US Date of print: 06.03.2014

Page: 3 of 5

# 8. Exposure controls / personal protection

#### **Exposure guidelines**

Occupational exposure limit values:

CAS No. Designa	ation Type	Limit value	
56-81-5 Glycero	USA: OSHA: TWA USA: OSHA: TWA	15 mg/m³ (total) 5 mg/m³ (respirable fraction)	

#### **Engineering controls**

Provide good ventilation and/or an exhaust system in the work area.

See also information in chapter 7, section storage.

Tightly sealed goggles according to OSHA Standard - 29 CFR: 1910.133 or ANSI Z87.1-2010. Eye protection:

Wear suitable protective clothing. Body protection:

Protective gloves according to OSHA Standard - 29 CFR: 1910.138.

Glove material: natural rubber, nitrile rubber, butyl caoutchouc (butyl rubber).

Breakthrough time >= 480 min.

Observe glove manufacturer's instructions concerning penetrability and breakthrough time.

#### Personal protection equipment

Respiratory protection must be worn whenever the TLV (WEL) levels have been exceeded. Respiratory protection:

Use filter type A (= against vapors of organic substances) according to OSHA Standard - 29

CFR: 1910.134 or ANSI Z88.2.

#### General protection and hygiene measures

Change contaminated clothing. After work, wash hands and face.

# 9. Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance: Physical state: liquid

Color: colorless

odorless Odor

pH value: at 20 °C: approx. 6 Initial boiling point and boiling range: approx. 120 °C Flash point/flash point range: approx. 180 °C

Density: at 20 °C: approx. 1.2 g/mL

Water solubility: at 20 °C: soluble

**Additional information** 

approx. 430 °C Ignition temperature:

## 10. Stability and reactivity

Reactivity: no data available

Chemical stability: Product is stable under normal storage conditions.



in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

# Conductivity Standard 100 mS/cm Material number 238935

Revision date: 28.03.2012 Version: 2 Language: en-US Date of print: 06.03.2014

Page: 4 of 5

Possibility of hazardous reactions

No hazardous reactions known.

Conditions to avoid: Protect from excessive heat.

Materials to avoid: strong oxidizing agents, nitric acid, sulphuric acid, phosphorus oxides, peroxides, halogens.

Hazardous decomposition products:

In the event of a fire, the following may be produced when the water evaporates: Carbon

monoxide and carbon dioxide.

# 11. Toxicological information

## **Toxicological tests**

Toxicological effects: Acute toxicity (oral): Lack of data.

Acute toxicity (dermal): Lack of data.

Acute toxicity (inhalative): Lack of data.

Skin corrosion/irritation: Lack of data.

Eye damage/irritation: Lack of data.

Sensitisation to the respiratory tract: Lack of data.

Skin sensitisation: Lack of data.

Germ cell mutagenicity/Genotoxicity: Lack of data.

Carcinogenicity: Lack of data.

Reproductive toxicity: Lack of data.

Effects on or via lactation: Lack of data.

Specific target organ toxicity (single exposure): Lack of data. Specific target organ toxicity (repeated exposure): Lack of data.

Aspiration hazard: Lack of data.

**Symptoms** 

After ingestion of high quantities: Headache, nausea, inebriation, vomiting, abdominal pain,

drowsiness, diarrhea.

**General remarks** 

After ingestion of high quantities: Headache, nausea, inebriation, vomiting, abdominal pain,

drowsiness, diarrhea.

# 12. Ecological information

#### Additional ecological information

General information: Do not allow to enter into ground-water, surface water or drains.

# 13. Disposal considerations

#### **Product**

Recommendation: Dispose of waste according to applicable legislation.

#### Contaminated packaging

Recommendation: Dispose of waste according to applicable legislation.

Non-contaminated packages may be recycled.



in accordance with 29 CFR 1910.1200 and ANSI standard Z400.1-2010

Revision date: 28.03.2012 Version: 2 Language: en-US Date of print: 06.03.2014

# Conductivity Standard 100 mS/cm

Material number 238935 Page: 5 of 5

## 14. Transport information

**USA: Department of Transportation (DOT)** 

Proper shipping name: Not controlled under DOT

Sea transport (IMDG)

Proper shipping name: Not restricted

Marine pollutant: No

Air transport (IATA)

Proper shipping name: Not restricted

**Further information** 

No dangerous good in sense of these transport regulations.

# 15. Regulatory information

#### **U.S. Federal Regulations**

Glycerol: TSCA Inventory: listed

TSCA HPVC: not listed

Clean Air Act:

SOCMI Chemical: yes NIOSH Recommendations:

Occupational Health Guideline: 0302

#### National regulations - EC member states

#### Labeling (67/548/EEC or 1999/45/EC)

Code letter and hazard symbol:

not applicable

R phrase(s): not applicable
S phrase(s): not applicable

#### National regulations - Great Britain

Hazchem-Code: -

## 16. Other information

Hazard rating systems: NFPA Hazard Rating:



Health: 1 (Slight)
Fire: 0 (Minimal)
Reactivity: 0 (Minimal)
HMIS Version III Rating:
Health: 1 (Slight)

Flammability: 0 (Minimal)
Physical Hazard: 0 (Minimal)

Personal Protection: X = Consult your supervisor

Reason of change: General revision
Date of first version: 20.04.2011

Department issuing data sheet

Contact person: see section 1: Dept. responsible for information

The information in this data sheet has been established to our best knowledge and was up-to-date at time of revision. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.

