General Specifications

Models AR-PX and AR-WX Outdoor-installed Waterproof Boxes (for a Single Arrester)

GS 77M02Y01-01E


■ GENERAL

This document explains the general specifications of the AR-PX and AR-WX outdoor-installed waterproof boxes for housing a single arrester.

■ ARRESTER MODELS THAT CAN BE HOUSED

AR-SA, AR-HA AR-TC, AR-RT AR-SY, AR-LP AR-HP, AR-SP AR-PS, AR-PH AR1-B2

■ MODELS AND SUFFIX CODES



■ MOUNTING AND APPEARANCE

Construction: Compatible with IP56 protection

Material: Main unit= Glass-reinforced unsaturated

polyester resin finished with deep-green

coating

Front cover = Stainless steel finished with

deep-green coating

Mounting bracket = Stainless steel

Mounting method:


Mounted on a JIS 50A (2-inch) pipe or a wall

External dimensions:

141.5 mm (H) \times 138 mm (W) \times 84 mm (D) (main unit only, excluding mounting brackets, cable glands and protrusions)

Weight: Approximately 1.9 kg (AR-PX) and 1.1 kg

(AR-WX)



■ ACCESSORIES

M4 screws for mounting an arrester: 2
Pipe-mounting bracket: 1 — for AR-PX only
M5 screws, flat washers and spring washers (used to fix
the pipe-mounting bracket): 2 pieces each — for AR-PX
only

U-shaped bracket assembly: 1 (one U-shaped bracket and two M8 nuts) — for AR-PX only



44

217

Supplied U-shaped


(109)

(125)

■ EXTERNAL DIMENSIONS

<AR-PX for Pipe Mounting>

Fixing the Mounting Bracket



Vertical Mounting

(181)


138 118 (146)(181) (181) Supplied U-shaped bracket (231) 217 2 0 23.5 23.5 50 50 50 70 Supplied M8 (109) Supplied M8 nuts in two places nuts in two places 120 (125) 32 M4-threaded external M4-threaded external grounding terminal

Horizontal Mounting

<AR-WX for Wall Mounting>

grounding terminal

Wall Mounting



• The information contained herein is subject to change without prior notice for the purpose of improving product quality and/or performance.