

Type code

Type code

**Measuring range / Overload protection**

A	-1 ... 0 bar / 5 bar
B	-1 ... +1 bar / 5 bar
C	0 ... +6 bar / 15 bar
D	0 ... +10 bar / 15 bar
F	-1 ... +10 bar / 15 bar

**Process connection**

G	Underside: G ¼ female thread; rear: G ¼ female thread
C	Underside: Push-in fitting for 4 mm pneumatic hose, rear: G ¼ female thread
N	Bottom: ¼" NPT female thread, pre-installed NPT adapter in G ¼ female thread; rear: G ¼ female thread

**Output signals / Electrical connection**

	Switching output 1	Switching output 2	Analog output	
A	PNP / NPN / Push-Pull	PNP / NPN / Push-Pull	-	/ M12 x 1, 4-pin
B	PNP / NPN / Push-Pull	-	4 ... 20 mA / 0 ...10 V	/ M12 x 1, 4-pin
C	PNP / NPN / Push-Pull	PNP / NPN / Push-Pull	4 ... 20 mA / 0 ...10 V	/ M12 x 1, 5-pin
D	IO-Link/PNP	PNP / NPN / Push-Pull	-	/ M12 x 1, 4-pin
F	IO-Link/PNP	PNP / NPN / Push-Pull	4 ... 20 mA / 0 ...10 V	/ M12 x 1, 5-pin
G	PNP	PNP / NPN / Push-Pull	4 ... 20 mA / 0 ...10 V	/ M12 x 1, 5-pin, additional function: leakage tester



Not all variants of the type code can be combined!