

ES-762

- “EZ Setup”- Guided Setup for First Time Users
- Utility Metering of Steam and Heating or Cooling Water Energy
- Two Auxiliary 4-20mA Analog Inputs
- Four Auxiliary Pulse Inputs and Totalizers for Secondary Measurement of Total from other meters
- Menu Selectable Hardware & Software Features
- Internal Data Logging
- Isolated Pulse and Analog Outputs Standard
- RS-232 Port Standard, Provides Power for Modem
- RS-485 Modbus RTU
- Internal Communication Card Option
Supports: BACnet IP, BACnet MS/TP, Metasys N2, Modbus TCP, AB Ethernet IP, AB DF1, LonWorks*
- Windows™ Setup Software
- Supports Most Flowmeter Types
- Stacked DP Transmitters Supported

Description:

The ES-762 Flow Computer primarily satisfies the instrument requirements for a variety of flowmeter types in liquid, steam and heat applications. Multiple flow equations are available in a single instrument with many advanced features. Two auxiliary current and four totalizer inputs are provided for secondary measurements.

The alphanumeric display offers measured parameters in easy to understand format. Manual access to measurements and display scrolling is supported

The versatility of the Flow Computer permits a wide measure of versatility within the instrument package. The various hardware inputs and outputs can be “soft” assigned to meet a variety of common application needs. The user “soft selects” the usage of each input/output while configuring the instrument. Multichannel auxiliary inputs can gather other information from site.

Applications Include:

Steam Mass, Steam Heat, Chilled Water Only, Heated Water Only including Low DeltaT cutoff.

The isolated analog output can be chosen to follow the volume flow, heat flow, mass flow, temperature, pressure, or density by means of a menu selection. Most hardware features are assignable by this method.

The user can assign the standard RS-232 Serial Port for external data logging, transaction printing, or for connection to a modem for remote meter reading.

A Service or Test mode is provided to assist the user during start-up system check out by monitoring inputs and exercising outputs. The system setup can also be printed.

* LonWorks protocol requires a different module assembly from the other available protocols. LonWorks is not field selectable.

Utility Metering Flow Computer with Multichannel Aux. Inputs & Totalizers



- DDE Server & HMI Software Available
- Remote Metering Solutions
- Optional - Attractive Wall Mount Enclosure

Specifications:

Environmental

Operating Temperature: 0 to +50 C
Storage Temperature: -40 to +85 C
Humidity : 0-95% Non-condensing
Materials: UL, CSA, VDE approved

Display

Type: 2 lines of 20 characters
Types: Backlit LCD. OLED and VFD ordering options
Character Size: 0.2” nominal
User selectable label descriptors and units of measure

Keypad

Keypad Type: Membrane Keypad with 16 keys
Keypad Rating: Sealed to NEMA 4X / IP65

Enclosure

Enclosure Options: Panel & Wall Mounting Styles
Size: See Dimensions
Depth behind panel: 6.5” including mating connector
Type: DIN
Materials: Plastic, UL94V-0, Flame retardant
Bezel: Textured per matt finish

Power Input

The factory equipped power option is internally fused. An internal line to line filter capacitor is provided for added transient suppression. MOV protection for surge transient is also supported

Universal AC Power: 85 to 276 Vrms, 50/60 Hz
DC Power Option: 24 VDC (16 to 48 VDC)

Power Consumption

AC Power: 6.5 V/A
DC Power: 300 mA max.

Flow Meter Types:

Linear: Vortex, Turbine, Positive Displacement, Magnetic, GilFlo, ILVA, Ultrasonic, Mass Flow and others
Square Law: Orifice, Venturi, Nozzle, V-Cone, Wedge, Averaging Pitot, Target, Accelabar and others
Multi-Point Linearization: May be used with all flowmeter types. Including: 16 point, UVC and dynamic compensation.

Flow Inputs for Primary Flow Computations:

Analog Input:

Accuracy: 0.02% FS at 20° C

Ranges

Voltage: 0-10 VDC, 0-5 VDC, 1-5 VDC

Current: 4-20 mA, 0-20 mA,
4-20 mA stacked, 0-20 mA stacked

Basic Measurement Resolution: 16 bit

Update Rate: 4 updates/sec

Automatic Fault detection: Signal over/under-range,
Current Loop Broken

Calibration: Operator assisted learn mode

Extended calibration: Learns Zero and Full
Scale of each range

Fault Protection:

Fast Transient: 500 V Protection (capacitive clamp)

Reverse Polarity: No ill effects

Over-Voltage Limit: 50 VDC Over voltage
protection

Over-Current Protection: Internally current limited
protected to 24VDC

Pulse Inputs:

Number of Flow Inputs: one

Input Impedance: 10 k Ω nominal

Trigger Level: (menu selectable)

High Level Input

Logic On: 2.5 to 30 VDC

Logic Off: 0 to 2 VDC

Low Level Input (mag pickup)

Selectable sensitivity: 10 mV and 100 mV

Minimum Count Speed: 0.25 Hz (to maintain rate
display)

Maximum Count Speed: Selectable: 0 to 50 kHz

Overvoltage Protection: 50 VDC

Secondary Totalizer Aux. Inputs:

Input Type: Contact Closure / Pulse

Number of Contact Closure / Pulse Inputs: four (4)

Input Impedance: 4.7 k Ω nominal

Trigger Level:

High Level Input

Logic On: 4 to 30 VDC

Logic Off: 0 to 1 VDC

Maximum Count Speed: 25 Hz

Excitation Voltage: 5 VDC

Overvoltage Protection: 30 VDC

User defined: units, scaling, rollover limit, labels

Uses: Cold Water, Natural Gas, Hot Water, Electric
kW-Hr

Temperature, Pressure, Density, and Aux 3/4 Inputs

The compensation inputs usage are menu selectable for temperature, temperature 2, pressure, density or not used. In addition, two auxiliary inputs are provided for secondary measurements.

Calibration: Operator assisted learn mode

Operation: Ratiometric

Accuracy: 0.02% FS at 20° C (current input)

Basic Measurement Resolution: 16 bit

Update Rate: 2 updates/sec minimum

Automatic Fault detection:

Signal Over-range/under-range

Current Loop Broken

RTD short

RTD open

Reverse Polarity: No ill effects

Over-Current Limit

(current input) Internally limited to protect input to
24 VDC)

Available Input Ranges (menu selectable)

Current: 4-20 mA, 0-20 mA (4 inputs)

Resistance: 100 Ohms DIN RTD (2 inputs)

100 Ohm DIN RTD (DIN 43-760, BS 1904):

Three Wire Lead Compensation

Internal RTD linearization learns ice point resistance

1 mA Excitation current with reverse polarity
protection

Temperature Resolution: 0.01 C

Accuracy: 0.5° C

Stored Information (ROM)

Steam Tables (saturated & superheated),

Fluid Properties: Water, or Generic with user entries of
fluid properties

User Entered Stored Information (EEPROM / Nonvolatile RAM)

Transmitter Ranges, Signal Types

Fluid Properties

(reference density, expansion factor, specific heat,
viscosity, isentropic exponent, combustion heating
value)

Units Selections (English/Metric)

Excitation Voltage

24 VDC @ 140 mA (fault protected)

Relay Outputs

The relay outputs usage is menu assignable to (Individually for each relay) Hi/Lo Rate Alarm, Hi/Lo Temperature Alarm, Hi/Lo Pressure Alarm, Pulse Output (pulse options), Aux.3, Aux.4, Wet Steam or General purpose warning (security).

Number of relays: 2

Contact Style: Form C contacts

Contact Ratings: 240 V, 5 amp

Analog Outputs

The analog outputs are menu assignable to correspond to the Uncompensated Volume Rate, Aux.3, Aux.4, Mass Rate, Heat Rate, Temperature, Density, or Pressure.

Number of Outputs: 2

Type: Isolated Current Sourcing (shared common)

Available Ranges: 0-20 mA, 4-20 mA (menu selectable)

Resolution: 16 bit

Accuracy: 0.05% FS at 20 Degrees C

Update Rate: 5 updates/sec

Temperature Drift: Less than 200 ppm/C

Maximum Load: 1000 ohms

Compliance Effect: Less than .05% Span

60 Hz rejection: 40 dB minimum

EMI: No effect at 3 V/M

Calibration: Operator assisted Learn Mode

Averaging: User entry of DSP Averaging constant to cause a smooth control action

Listing: CE Compliant, UL, C-UL Pending

Serial Communication

The serial port can be used for printing, datalogging, modem connection and communication with a computer. Power is provided for KEP's MPP2400N (modem) communication accessory.

RS-232:

Device ID: 01-99

Baud Rates: 300, 1200, 2400, 9600

Parity: None, Odd, Even

Handshaking: None, Software, Hardware

Print Setup: Configurable print list and formatting,
Compatible with external dataloggers.

RS-485:

Device ID: 01-247

Baud Rates: 300, 1200, 2400, 4800, 9600, 19200

Parity: None, Odd, Even

Protocol: Modbus RTU (Half Duplex)

Data Logging

The data logger captures print list information to internal storage for approximately 5000 transactions. This information can be used for later uploading or printing. Storage format is selectable for Comma-Carriage Return or Printer formats.

Isolated Pulse output

The isolated pulse output is menu assignable to Uncompensated Volume Total, Heat Total or Mass Total.

Pulse Output Form (menu selectable): Open Collector

NPN or 24 VDC voltage pulse

Nominal On Voltage: 24 VDC

Maximum Sink Current: 25 mA

Maximum Source Current: 25 mA

Maximum Off Voltage: 30 VDC

Saturation Voltage: 0.4 VDC

Pulse Duration: User selectable

Pulse output buffer: 8 bit

Fault Protection

Reverse polarity: Shunt Diodes

Over-current Protected

Over-voltage Protected

Real Time Clock

The Flow Computer is equipped with a battery backed non-volatile real time clock with display of time and date.

Format:

24 hour format for time

Day, Month, Year for date

Internal Multi-protocol Communication Card Option

FEATURES

- Internal communication card eliminates the need for external protocol converters.
- Supports: BACnet IP, BACnet MS/TP, Metasys N2, Modbus TCP, AB Ethernet IP, AB DF1, LonWorks*
- Easy to configure via the Web Interface.
- Dedicated internal LonWorks is also available
- Dedicated internal RS485 Modbus RTU is also available

DESCRIPTION

The multi-protocol communication card is an internal, high performance, Building Management System communication solution for the ST2 flow computer family. The card provides an instant interface, enabling the KEP flow computers to communicate with multiple BMS protocols, including:

- BACnet MS/TP
- BACnet IP
- Modbus TCP
- Metasys N2
- AB DF1
- AB EtherNet/IP
- LonWorks*

CONFIGURATION

Use a web browser to locate the internal web page and configure the settings. The detailed settings vary with the different communication protocols. Only one communication port/protocol can be used. A web browser is also used to configure the site specific settings for each instrument




Fig 1

Top view of multi-protocol card installed on ES762 mother board




Fig 2

Rear view of ES762 case.
Communication ports are available for RS-485 and Ethernet

* LonWorks protocol requires a different module assembly from the other available protocols. LonWorks is not field selectable.

Configuration Parameters


Parameter Name	Parameter Description	Value	
protocol_select	Protocol Selector Set to 1 for BACnet IP Set to 2 for BACnet MSTP Set to 3 for Metasys N2 Set to 4 for Modbus TCP Set to 5 for EtherNet/IP Set to 6 for DF1	<input type="text" value="1"/>	Submit
node_offset	BACnet Node Offset This is used to set the BACnet device instance. The device instance will be sum of the Modbus device address and the node offset. <i>(0 - 4194303)</i>	<input type="text" value="50000"/>	Submit
bac_ip_port	BACnet IP Port This sets the BACnet IP port of the Gateway. The default is 47808. <i>(1 - 65535)</i>	<input type="text" value="47808"/>	Submit
bac_cov_option	BACnet COV This enables or disables COVs for the BACnet connection. Use COV_Enable to enable. Use COV_Disable to disable. <i>(COV_Enable/COV_Disable)</i>	<input type="text" value="COV_Disable"/>	Submit
bac_bbmd_option	BACnet BBMD This enables BBMD on the BACnet IP connection. Use BBMD to enable. Use - to disable. The bdt.ini files also needs to be downloaded. <i>(BBMD/-)</i>	<input type="text" value="-"/>	Submit

Active profiles

Nr	Node ID	Current profile	Parameters	
1	1	BAC_IP_SUPERtrol_II		Remove
Add				


Sample screen shot of web interface configuration

Standard Dimensions



Dimensions are in inches (mm)


Wall Mount (“W” mounting option) Dimensions



Terminal Designations

1	DC OUTPUT	1	FLOW IN
2	PULSE IN lin (+)	2	TEMPERATURE IN
3	lin (+)	3	AUX - 4
4	COMMON	4	PRESSURE (TEMP 2)
5	RTD EXCIT (+)	5	RTD SENS (+)
6	RTD SENS (+)	6	RTD SENS (-)
7	RTD SENS (-)	7	PULSE OUTPUT (+)
8	lin (+)	8	PULSE OUTPUT (-)
9	RTD EXCIT (+)	9	ANALOG OUTPUT 1 (+)
10	RTD SENS (+)	10	ANALOG OUTPUT 2 (+)
11	RTD SENS (-)	11	ANALOG OUTPUT COMMON (-)
12	RTD SENS (-)	12	NO
13	PULSE OUTPUT (+)	13	COM RLY1
14	PULSE OUTPUT (-)	14	NC
15	ANALOG OUTPUT 1 (+)	15	NC
16	ANALOG OUTPUT 2 (+)	16	COM RLY2
17	ANALOG OUTPUT COMMON (-)	17	NO
18	NO	18	AC LINE DC (+)
19	COM RLY1	19	AC LINE DC (-)
20	NC	20	
21	COM RLY2	21	
22	NO	22	
23	AC LINE DC (+)	23	
24	AC LINE DC (-)	24	

Terminal Layout



Ordering Information

Ex: ES762ST2 L 1 1 P 13 TB QDI

Series: ES762ST2 = Utility Metering Flow Computer

Display Type: L= LCD, O= OLED, V= VFD

Input Type: 1= 85 to 276 VAC, 3= 24 VDC (16 to 48 VDC)

Network Card: 1= RS485/Modbus (standard), 3= COM CARD with Multi-Protocol
Specify protocol (example: **3 BAC/IP**)
BAC/IP = BACnet IP
BACMS/TP = BACnet MS/TP
MOD/IP = Modbus TCP/IP
METASYS/N2 = Metasys N2
ABDF1 = AB DF1
ABETH/IP = AB EtherNet/IP
4= COM CARD with LonWorks Protocol
Specify protocol (example: **4 LONWORKS**)
Factory configuration of network card settings

Mounting: P= Panel Mount, *N= NEMA 4 Wall Mount (see NEMAtr0l & MS811), *W= NEMA 12/13 Wall Mount w/ Clear Cover

Options: 13 = Superchip; 2 relay, Positive heat only (standard)
TB= RS485 Terminal Block standard for Panel Mount (P) and NEMA4 Wall (N) Mounting Styles
QDI=Quad Digital Input

Accessories:
 OPC/DDE Server for RS232 Port available, see EX5-UCOND-NA00
 OPC/DDE Server for Modbus Suite available, see EX5-MDBUS-NA00
 Modem Available, see MPP-56KN and MPP-2400N
 Serial printer available, see P20, P220, P295
 Ethernet Port Server available, see IEPS
 Ethernet Port Server Modbus TCP available, see ADAM4572
 RS-422/485 to RS-232 Communication Adapter available, see CA285
 RS232 Extender Cable: P/N=13220-
 <length in inches>